VertiLine63D
Rack Mount DC Power Supply

Rev. DSVertiLine63D - 07182012

Overview

Altronix Vertiline63D Rack Mount DC Power Supply provides sixteen (16) filtered and electronically regulated power outputs in a space saving 1U EIA 19” rack mount chassis. This unit is available with 24VDC power outputs. Vertiline Rack Mount Power Supplies are also available in eight (8) outputs.

VertiLine63D

VERTILINE™

Specifications

Input:

- 115VAC 60 Hz, 3 amp input.

Output:

- 24VDC outputs rated @ 8 amp total current max. *(0.5 amp per device, 2.5 amp max.).*
- Sixteen (16) PTC protected power outputs.
- Filtered and electronically regulated.

Electrical:

- Operating temperature: -20º C to 49º C ambient.
- 98.95 BTU/Hr.
- System AC input VA requirement: 345VA.

Mechanical:

- Units can be rack, wall or shelf mounted.

Mechanical *(cont’d)*:

- Modular 1U standard EIA 19” rack mount chassis
- Enclosure Dimensions (H x W x D approx.): 1.625” (41.275mm) x 19.125” (486mm) x 8.5” (216mm)
- Product weight (approx.): 7.2 lbs. (3.27 kg.).
- Shipping weight (approx.): 8.3 lbs. (3.76 kg.).

Features:

- Sixteen (16) power LEDs.
- Illuminated master power disconnect circuit breaker with manual reset.
- IEC 320 - 3-wire grounded line cord (detachable).
- Removable terminal blocks with locking screw flange.

Agency Approvals

CE European Conformity

Enclosure Dimensions *(H x W x D) (approximate)*:

1.625” (41.275mm) x 19.125” (486mm) x 8.5” (216mm)